

In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: GUM ROSIN (ALL GRADES) GUM ROSIN 8050-09-7 232-

Chemical Name: 475-7 Adhesives, Printing Ink, etc. COLOPHONY,

CAS Number: TRICYCLIC MONOCARBOXYLIC ACIDS None known.

**EINECS Number:** 

**Relevant Identified Uses:** 

Synonyms:

Uses Advised Against:

ARTISANAT BUB INC

Company name: 10141 Ave de London, Montreal-

Address: Nord, H1H4H4, Quebec,

**CANADA** 

**Phone Number:** 

Fax Number: 4504996882

Emergency Phone Number: info@pinovillage.com

E-mail:

### 2. HAZARDS IDENTIFICATION

## SIGNAL WORD: WARNING



GHS07



GHS08

Classification of the substance or mixture:

ACUTE DERMAL TOXICITY, CATEGORY 5
ACUTE INHALATION (DUST) TOXICITY, CATEGORY 4

**SKIN SENSITIZER, CATEGORY 1** 

**RESPIRATORY SENSITIZER, CATEGORY 1** 

**SKIN IRRITANT, CATEGORY 3** 



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

### **EYE IRRITANT, CATEGORY 2B**

HAZARDOUS TO THE AQUATIC ENVIRONMENT, LONG-TERM (CHRONIC), CATEGORY 4

**HAZARD STATEMENTS** 

PHYSICAL HAZARDS: NONE

HEALTH HAZARDS: H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

H332 - Harmful if inhaled

ENVIRONMENTAL HAZARDS: H413 - May cause long lasting harmful effects to aquatic life

PRECAUTIONARY STATEMENTS

PREVENTION: P210 - Keep away from heat / sparks / open flames / hot surfaces.

No smoking

P233 - Keep container tightly closed

P261 - Avoid breathing dust / fume / gas / mist / vapors / spray

P262 - Do not get in eyes, on skin, or on clothing P264 - Wash hands thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves / protective clothing / eye protection /

face protection

RESPONSE: P301 + P310 - If swallowed: immediately call a poison center or

doctor / physician

P302 + P352 - If on skin: wash with plenty of soap and water

P330 - RINSE MOUTH

**P331 - DO NOT INDUCE VOMITING** 

P333 + P313 - If skin irritation or rash occurs: get medical

advice / attention

P362 - Take off contaminated clothing and wash before reuse

P403 + P233 + P235 - Store in a well-ventilated place. Keep container

tightly closed. Keep cool.

P501 - Dispose of contents / container to approved disposal facility

DISPOSAL: or site

OTHER INFORMATION

STORAGE:

SOLID RESIN HAZARDS: No physical / chemical, environmental or human hazards are reported

or known. OSHA has listed gum rosin as a "sensitizer" with the



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

warning statement: "reduce exposure to as low as possible."

However, there is no set Threshold Limit Value (TLV).

MOLTEN RESIN HAZARDS: Vapors emitted when the resin is heated can cause respiratory

problems. Fumes from hot resin, at high temperatures, can have

an irritating effect on eyes.

Refer to Section 15 for other regulations.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Molecular Formula: C20H30O2

EC/UPAC NAME	CAS	EINECS	WEIGHT %	SYMBOL	R PHASES	S PHASES
Gum Rosin	8050-09-7	232-475-7	>85%	Xi	See Section 15	See Section 15
Un- saponifiable Matter	N/A	N/A	<15%	N/A	See Section 15	See Section 15

## 4. FIRST AID MEASURES

AFTER INHALATION: Supply fresh air. Vapors may cause slight irritation. If

symptoms are experienced, get medical attention. In case of unconsciousness, place patient in stable side

position for transportation.

AFTER INGESTION: DO NOT INDUCE VOMITING.

Immediately call a doctor / physician.

AFTER SKIN CONTACT: Immediately rinse with plenty of water. Wash the

product powder away with soap. For contact with melted rosin, cool the affected area immediately, do not try to remove the rosin plaques from the skin. Get medical attention if irritation or skin rash occurs. Remove contaminated clothing and footwear. Wash clothing before use. Clean footwear thoroughly before

use.



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

**AFTER EYE CONTACT:** 

Immediately rinse with plenty of water. Remove contact lenses if present and easy to do. Hold eyelids apart and flush eyes with plenty of cool low-pressure water for at least 15 minutes. Get immediate medical attention if discomfort persists.

## 5. FIRE FIGHTING MEASURES

FLAMMABILITY OF THE PRODUCT: COMBUSTIBLE (AVOID GENERATION OF DUST)

FLASH POINT: >205°C (>400°F)

**EXTINGUISHING MEDIA:** 

☑ SUITABLE: WATER FOG / SPRAY, DRY CHEMICAL (CLASS B),

**REGULAR FOAM, CO2** 

□ UNSUITABLE: UNKNOWN

HAZARDOUS THERMAL DECOMPOSITION

PRODUCTS:

Thermal decomposition may generate carbon monoxide, carbon dioxide and other unidentified

organic compounds.

SPECIAL PROTECTIVE EQUIPMENT FOR

FIREFIGHTERS:

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

PERSON-RELATED SAFETY PRECAUTIONS: Do not breathe material-related dust. Avoid generating

dust when handling this product. Wear personal protective equipment. Evacuate unprotected persons to safe areas. Provide adequate ventilation. Remove all

sources of ignition.

MEASURES FOR

**ENVIRONMENTAL PROTECTION:** 

This material is not biodegradable. Avoid allowing the product or by-products to reach soil, waterways,

drains and sewers. Inform the relevant authorities if the

product has caused environmental pollution (soil,

waterways, drains or sewers).

**MEASURES FOR CLEANING / COLLECTING:** 

SOLID: Collect solid materials in appropriate container and



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

label for proper disposal. In situations where the material remains uncontaminated, the material may be collected for use.

LIQUID (MOLTEN): Allow liquid material to cool then collect cooled solids.

Place materials in an appropriate container and label

for proper disposal or use, depending on

contamination of material.

### 7. HANDLING AND STORAGE

**HANDLING:** Wear personal protective equipment. Provide adequate

> ventilation. Solid material is non-toxic. Vapors from liquid material may cause respiratory irritation. Keep product dust / fines away from heat, sparks, open

flames and hot surfaces.

STORAGE: Requirements for storage areas and containers: Store

in a cool well-ventilated place, away from heat sources.

### RECOMMENDED AND UNSUITABLE MATERIALS FOR STORAGE:

SUITABLE: Stainless steel, galvanized, aluminum drums; or bags

composed of approved materials.

**UNSUITABLE:** None known

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **CONTROL PARAMETERS:**

**OCCUPATIONAL EXPOSURE LIMITS: NOT AVAILABLE** 

**BIOLOGICAL EXPOSURE LIMITS: NOT AVAILABLE** 

DNEL: **NOT AVAILABLE** 

PNEC: **NOT AVAILABLE** 

**ENGINEERING MEASURES:** Provide local exhaust or general room ventilation to

> minimize exposure to vapors. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

PERSONAL PROTECTION:

EYES / FACE PROTECTION: Safety goggles (standard EN 166).

HAND PROTECTION: Protective gloves resistant to chemicals (standard EN

374-1). Gloves should be discarded and replaced if there is any indication of degradation or chemical

breakthrough.

BODY PROTECTION: Protective work clothing

RESPIRATORY PROTECTION: Use suitable respiratory protective device in case of

insufficient ventilation to reduce exposure to vapors

and/or material-related dust.

**GENERAL PROTECTIVE AND** 

**HYGIENIC MEASURES:** 

The usual precautionary measures are to be adhered to

when handling chemicals. Take off contaminated

clothing and wash before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Solid at 20°C

ODOR: Slight pine / resin aroma

ODOR THRESHOLD: Not available pH: Not applicable

ACID NUMBER: 147 – 167 (mg KOH/g)

MELTING POINT: 68 - 78°C (154.4 – 172.4°F)

FLASH POINT: >205°C (>400°F)

INITIAL BOILING POINT / BOILING RANGE:

Not available

EVAPORATION RATE: Not applicable

FLAMMABILITY: Combustible (Dust)

UPPER / LOWER FLAMMABILITY

OR EXPOLSIVE LIMITS:

Not available

VAPOR PRESSURE (@ 317°C):

VAPOR DENSITY: 100 mmHg

**SPECIFIC GRAVITY (H2O = 1):** 4.7 (air = 1)

PARTITION COEFFICIENT 1.06 - 1.09

N-OCTANOL / WATER (LOG VALUE): Log Pow: 1.9 - 7.7

WATER SOLUBILITY:

Insoluble



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

REFRACTION INDEX: **SELF-IGNITION** 1.54 at 20°C Not available **TEMPERATURE: DECOMPOSITION** TEMPERATURE: VISCOSITY: EXPLOSIVE Not available Not available PROPERTIES: OXIDIZING PROPERTIES: Not available **DISSOCIATION CONSTANT: STABILITY IN** Not available ORGANIC SOLVENTS AND **IDENTITY OF RELEVENT DEGRADATION** Not available

PRODUCTS:

Not available

### 10. STABILITY AND REACTIVITY

**CHEMICAL STABILITY:** No decomposition if used according to specifications.

Product is stable under normal conditions.

Does not present reactivity in contact with air or water. REACTIVITY:

Keep away from heat and sources of ignition. Avoid **CONDITIONS TO AVOID:** 

material dust dispersion in air.

Avoid contact with strong acids, alkalis, oxidizing **MATERIALS TO AVOID:** 

agents, and organic and inorganic peroxides. Thermal decomposition may generate carbon

**HAZARDOUS THERMAL** 

monoxide, carbon dioxide and other unidentified **DECOMPOSITION PRODUCTS:** 

organic compounds.

### 11. TOXICOLOGICAL INFORMATION

### **HUMAN HEALTH HAZARD ASSESSMENT**

Solid resin at normal temperatures presents no toxicological danger. No values of long term or chronic toxicity are available. Inhalation studies with rats submitted to decomposition fumes of this kind indicate low toxicity. At normal concentration of 1.50-2.00 mg/l of fumes, no deaths occurred after a six-hour exposure period.

### 12. ECOLOGICAL INFORMATION

#### **ECOTOXICITY:**

ACUTE TOXICITY (LC50): FISH (Brachydanio Rerio) 150 mg/L (96 h)



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200 238 mg/L (48 h)

185 mg/L (72 h)

**ACUTE TOXICITY (EC50): DAPHNIA Magna** 

ACUTE TOXICITY (EC50): ALGAE (Selenastrum capricornutum)

BIODEGRADABILITY: 32% biodegradable after 28 days

BIOACCUMULATIVE POTENTIAL: NOT AVAILABLE

MOBILITY IN SOIL: NOT AVAILABLE

### 13. CONSIDERATIONS ON WASTE TREATMENT AND DISPOSAL

PRODUCT: Dispose of in accordance with Federal, State and Local

environmental regulations. This product does not constitute a hazardous waste problem. Avoid inhalation of material-related dust and contact with skin & eyes. May form flammable dust / air mixtures.

UNCLEANSED PACKAGING: Disposal must be made according to local and national

regulations.

### 14. TRANSPORT INFORMATION

DOT HAZARD CLASS 65: NON-REGULATED CHEMICALS, NOI. (NON-HAZARDOUS)



NFPA CODES: HEALTH - 1, FIRE - 1, REACTIVITY - 0



**HMIS CODES** 

### 15. REGULATORY INFORMATION

This product is in compliance with inventory listing requirements of the U. S. Toxic Substance Control Act (TSCA) - Chemical Substance Inventory, EINECS - Europe, DSL - Canada, ENCS - Japan, AICS - Australia, IECS - China, PICCS - Philippines, and ECL - Korea.

Classification according to Directive 67/548/EEC - Annex I and Regulation (EC) N°1272/2008 - Annex VI



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200







#### **RISK PHRASES:**

R 20/21/22 HARMFUL BY INHALATION, IN CONTACT WITH SKIN, AND IF SWALLOWED.

R 36/37/38 IRRITATING TO EYES, RESPIRATORY SYSTEM, AND SKIN.

R 42/43 R MAY CAUSE SENSITIZATION BY INHALATION AND SKIN CONTACT.

52/53 HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE

EFFECTS IN THE AQUATIC ENVIRONMENT.

HARMFUL; MAY CAUSE LUNG DAMAGE IF SWALLOWED.

#### **SAFETY PHRASES:**

S 22 DO NOT BREATHE DUST.

S24/25 AVOID CONTACT WITH SKIN AND EYES.

S 36/37/39 WEAR SUITABLE PROTECTIVE CLOTHING, GLOVES AND EYE/FACE

PROTECTION.

S 46 IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS SDS

OR LABEL.

AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS / S 61

SAFETY DATA SHEETS.

IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK MEDICAL ADVICE

S 62 IMMEDIATELY AND SHOW THIS SDS OR LABEL.

#### ADDITIONAL REGULATORY INFORMATION

The following environmental and regulatory data are provided to assist users of this product in defining their regulatory environmental compliance obligations. Most resins produced from rosin are biologically inert & have a low order of toxicity. The extended use of these materials in printed inks has produced no ill effects from oral or dermal toxicity & meet FDA requirements for use in food packaging & as components of chewing gum, soft drinks, citrus coatings, flavoring compounds, rubber goods & many others.

### **SARA TITLE III**

SECTION 302,<sup>1</sup>EHS TPQ (LBS.): N/A<sup>2</sup>

SECTION 304,<sup>3</sup>EHS RQ (LBS.): N/A<sup>4</sup>

SECTION 311 / 312,5HAZARD NHH, NPH

CATEGORY:



In Compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200

SECTION 313, TOXIC CHEMICAL (YES,

NO

NO):

CERCLA (40 CFR 302.4 HAZARDOUS SUBSTANCE & REPORTABLE QUANTITIES):

Gum Rosin is NOT contain any hazardous substances

listed in 40 CFR 302.4

CALIFORNIA PROP. 65: Resins based on rosin-derived resins are NOT listed on

California's Prop. 65 toxic substance list.

RCRA INFORMATION: This product is not listed in federal hazardous waste

regulation 40 CFR 261.33, paragraph (e) or (f), i.e., chemical products that are considered hazardous if they become wastes. It does not exhibit any of the hazardous characteristics listed in 40 CFR 261, Subpart C. State or local hazardous waste regulations may apply if they are different from the federal regulation. This product is NOT

biodegradable.

ODC STATUS: Gum Rosin is NOT found to contain any ozone depleting

compounds since rosin by definition is non-volatile

resinous.

TSCA STATUS: Gum Rosin is included on the EPA TSCA Chemical

Substance Inventory.

DSL STATUS: Gum Rosin is included on Canada's Domestic Substance

List.

CANADIAN WHMIS: Gum Rosin is classified as a NON-CONTROLLED

PRODUCT according to our interpretation of the amendments to the Hazardous Products Acts.

FOOTNOTES: 1) SECTION 302 - Threshold Planning Quantity, Extremely Hazardous Substance (EHS), (40 CFR 355 Emergency Planning and Notification regulations).

2) N/A: This

chemical is not an EMS. Therefore, there is no Threshold Planning Quantity (TPQ). 3) SECTION 304 - Reportable Quantity for Releases of an EMS (40 CFR 355, Appendix A). 4) N/A: This chemical is not an EMS. Therefore, there is no Reportable Quantity (RQ). 5) SECTION 311/312 - 40 CFR 370 Hazardous Chemical Reporting Requirements "Hazard Categories": HC-1 - Immediate (acute) health hazard, HC-2 - Delayed (chronic) health hazard, HC-3 - Fire hazard, HC-4 - Sudden release of pressure hazard, HC-5 - Reactive hazard, NHH - Not a health hazard, NPH - Not a physical hazard.

### 16. OTHER INFORMATION

ARTISANAT BUB Inc. believes that such information is accurate and reliable as of the date of this SDS, but no representation, guarantee or warranty, expressed or implied, is made to the accuracy, or completeness of the information. ARTISANAT BUB Inc. urges users receiving this information to make their own determination as to the data's suitability and completeness for their particular application.